



H2O Rx

Spectacle Blind

Spectacle Blinds are simple devices for positive pipeline isolation. Clamped between two flanges, the spectacle blind can be rotated into and out of the pipeline to put in into or out of service.

We have standardised on 316 S/S, and have designs for ANSI and AS4087 flanges. Other flange types can be accommodated on request.



Part Number	Size (DN)	Flange Spec	Thickness
S0124-DN25-ANSI 150#	25	ANSI 150#	6
S0124-DN40-ANSI 150#	40	ANSI 150#	6
S0124-DN50-ANSI 150#	50	ANSI 150#	6
S0124-DN50-AS4087 PN16	50	AS4087 PN16	6
S0124-DN80-ANSI 150#	80	ANSI 150#	6
S0124-DN80-AS4087 PN16	80	AS4087 PN16	6
S0124-DN100-ANSI 150#	100	ANSI 150#	10
S0124-DN100-AS4087 PN16	100	AS4087 PN16	10
S0124-DN150-ANSI 150#	150	ANSI 150#	10
S0124-DN150-AS4087 PN16	150	AS4087 PN16	10
S0124-DN200-ANSI 150#	200	ANSI 150#	16
S0124-DN200-AS4087 PN16	200	AS4087 PN16	16
S0124-DN250-ANSI 150#	250	ANSI 150#	16
S0124-DN250-AS4087 PN16	250	AS4087 PN16	16
S0124-DN300-ANSI 150#	300	ANSI 150#	20
S0124-DN300-AS4087 PN16	300	AS4087 PN16	20
S0124-DN350-ANSI 150#	350	ANSI 150#	22



H2O Rx

Phone: 0409 784 236

Web: www.h2orx.com.au

Literature Request: S0124 - Spectacle Blind

Email: info@h2orx.com.au